

# FS-2000D Specifications

## basic specifications:

Configuration:	Small Workgroup Monochrome Printer with Standard Duplex Unit, 500 Sheet Drawer plus 100 Sheet Multi-Purpose Tray
Resolution:	Fine 1200 mode (1,200 x 1,200 dpi), Fast 1200 mode (1,800 x 600 dpi), 600 x 600 dpi, 2,400 x 600 dpi Interpolated (w/KIR)
Printer Memory:	Standard 64MB, upgradable to 576MB via 100 pin DDR DIMMs, Standard CF Card Slot (Type 1), Micro Drive Slot
Electrical Requirements:	120V, 60Hz, 7.6A
Dimensions:	15.04"W x 15.51"D x 11.22"H
Weight:	34.83 lbs
Max Duty Cycle:	150,000 pages per month

## controller specifications:

Controller:	PowerPC440 400 MHz
Supported PDL / Emulations:	PRESCRIBE, PCL6 (XL, 5e, P JL), KPDL3 (PS3), Diablo 630, IBM ProPrinter X24E, Epson LQ850, Line Printer
Fonts:	80 Outline Fonts for PCL6/KPDL3, 1 Bitmap Font
Windows® OS Compatibility:	Windows® 95/98/Me/NT4.x/2000/XP/2003
Novell® OS Compatibility:	Novell Netware® 3.x/4.x/5.x/6.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)
Connectivity / Interface:	Hi-Speed USB 2.0, USB Host (Full), Bi-Directional Parallel IEEE1284
KUIO LV Enhancement Slot:	Optional IB-30 10/100BaseTX Network Interface, IB-11 RS-232C Serial
Supported Protocol:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers
Utilities:	KM-NET Viewer, KM-NET for Clients, Kyocera Command Center, IC-Link, PDF Direct Print, KX SpoolCenter, PRESCRIBE Utilities

## output speeds:

Warm-Up Time:	Less than 10 Seconds (From Sleep Mode)
First Print Out:	Less than 9 Seconds (EcoFuser Off)
Pages Per Minute:	31 Letter, 26 Legal

## paper supply:

Standard Paper Sources:	500 Sheet Drawer, 100 Sheet MPT
Drawer Paper Size:	LTR, LGL, Oficio2, A4, A5, B5, A6, Folio
MPT Paper Size:	LTR, LGL, Oficio2, A4, A5, B5, A6, Folio Custom (2.8" x 5.8" - 8.5" x 14.0")
Std/Max Paper Capacity:	600 Sheets/1,100 Sheets
Paper Weight:	16 - 32 lb Bond via Paper Drawer, 16 lb Bond - 120 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

## paper handling options:

### paper drawer: PF-310

Paper Capacity:	500 Sheets
Max. Drawers:	1
Paper Weight:	16 - 32 lb Bond
Paper Size:	LTR, LGL, Oficio2, A4, A5, B5, A6, Folio
Dimensions/ Weight:	15.04"W x 15.51"D x 4.33"H / 8.6 lbs

## additional options:

Additional memory is available in 64, 128, 256, or 512 MB DDR DIMMs.

## consumables:

TK-312:	12,000 pages @ 5% Coverage * Ships with 6,000 pages @ 5% Coverage. ISO 19752 Certified
---------	-------------------------------------------------------------------------------------------



Specifications and design are subject to change without notice. All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc.  
225 Sand Road, PO Box 40008,  
Fairfield, NJ 07004-0008, USA  
©2006 Kyocera Mita America, Inc.  
[www.kyoceramita.com](http://www.kyoceramita.com)

