

FS-820 Specifications

basic specifications:

Configuration:	Desktop Monochrome Printer with Standard 250 Sheet Drawer plus Single Sheet Multi-Purpose Tray
Resolution:	Fast 1200 dpi (1800 x 600), 600 x 600 dpi, 2400 x 600 (w/KIR)
Printer Memory:	Standard 16MB, upgradable to 272MB via 100 pin DIMMs; Standard Internal CF Card Slot (Type 1)
Electrical Requirements:	120V, 60Hz, 6.8A
Dimensions:	15.0"W x 15.4"D x 9.6"H
Weight:	20.3 lbs
Max Duty Cycle:	12,000 Pages per month

controller specifications:

Controller:	PowerPC405 192 MHz
Supported PDL / Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL5e)
Fonts:	14 Fonts for PCL XL/5e, 1 Bitmap Font
Windows™ OS Compatibility:	Windows 9x/Me/NT4.x/2000/XP
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)
Connectivity / Interface:	Standard IEEE 1284 Parallel (Nibble/ECP), Full-Speed USB 2.0
Expansion:	Optional IB-100 External Print Server
Driver:	KX Driver for Windows, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver
Utilities:	K Print, PRESCRIBE Utilities

optional ib-100 print server:

Controller:	PowerPC405 192 MHz
Supported PDL / Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL5e)
Windows™ OS Compatibility:	Windows 98SE/Me/NT4.x/2000/XP
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)
Printer Interface:	Full Speed USB 2.0
Network Interface:	10/100BaseTX
Supported Protocol:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Utilities:	KM-NET Viewer, KM-NET for Clients, Kyocera Command Center, K Print, PRESCRIBE Utilities

output speeds:

Warm-Up Time:	Less than 16 Seconds
First Print Out:	Less than 11 Seconds
Pages Per Minute:	17 Letter / 16 A4 / 15 Legal

paper supply:

Standard Paper Sources:	250 Sheet Drawer, Single Sheet MPT
Drawer Paper Size:	8.5" x 11", 8.5" x 13", 8.5" x 14", A4, B5, A5
MPT Paper Size:	8.5" x 11", 8.5" x 13", 8.5" x 14", A4, B5, A5, Custom (2.8" x 5.8" - 8.5" x 14")
Paper Capacity:	251 Sheets
Paper Weight:	16-28 lb Bond via Paper Drawer, 16 lb Bond - 90 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

hardware options:

Memory:	Additional memory is available in 16, 32, 64, 128, or 256MB 100-Pin DIMMs.
---------	--

consumables:

TK-112:	6,000 pages @ 5% Coverage <small>* Ships with 3,000 pages @ 5% Coverage. ISO/IEC 19752 Compliant.</small>
---------	--



Specifications and design are subject to change without notice. All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc.
225 Sand Road, PO Box 40008,
Fairfield, NJ 07004-0008, USA
©2005 Kyocera Mita America, Inc.
www.kyoceramita.com/us

