

# FS-C8008N/DN Specifications

## BASIC SPECIFICATIONS:

FS-C8008N Configuration:	Color Network Printer with Standard Dual 500 Sheet Drawers, 150 Sheet Multi-Purpose Tray
FS-C8008DN Configuration:	Color Network Printer with Standard 500 Sheet Drawer, 150 Sheet Multi-Purpose Tray, Automatic Duplexing
Resolution:	Multi-Bit 600 x 600 DPI
Memory:	Standard 128MB, Upgradeable to 640MB via 100 Pin DIMMs. Standard HDD, Standard CF Card Slot (Type 1)
Electrical Requirements:	120V, 60Hz, 11.5A
Dimensions:	23.2"W x 23"D x 26.4"H
FS-C8008N Weight:	210.3 lbs
FS-C8008DN Weight:	216.9 lbs
Max. Duty Cycle:	25,000 / 100,000 pages per month

## CONTROLLER SPECIFICATIONS:

Controller:	Embedded PowerPC750 / 400 MHz Controller
Supported PDL / Emulations:	PRESCRIBE, KPDL3(PS3), PCL 6 (PCL 5c, PCL XL), KC-GL (HP-GL/2)
Fonts:	136 Outline Fonts for KPDL3, 80 Outlines Fonts for PCL 5c/XL, 1 Bitmap Font
Windows OS Compatibility:	Windows 95/98/Me/NT4.x/2000/XP
Novell OS Compatibility:	Novell NetWare 3.x/4.x/5.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard 10/100 BaseTX, Full-Speed USB2.0, Bi-Directional Parallel IEEE1284
KUIO LV Expansion Slot (2):	One Slot for Standard Hard Disk Drive, 2nd Slot for Optional: IB-11 Serial RS-232C; IB-20 10/100 BaseTX, 10Base2; or IB-22 Enhanced Wireless NIC
Supported Protocol:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows, PPD for Mac, and PPD for Linux/UNIX
Utilities:	KM-NET Viewer, PDF Direct Printing, KM-NET Remote Operation Panel, KM-NET Job Manager, KM-NET Printer Disk Manager, Network Advanced Setup Utilities, PRESCRIBE Utilities

## OUTPUT SPEEDS:

Warm-Up Time:	Within 180 Seconds
First Print Out: (Color / Mono):	28.0 / 17.0 Seconds
Pages Per Minute: (Color / Mono):	8 / 31 Letter, 4 / 15 Legal, 4 / 15 Ledger

## PAPER SUPPLY:

Standard Paper Sources:	FS-C8008N: Dual 500 Sheet Drawers, 150 Sheet MPT FS-C8008DN: 500 Sheet Drawer, 150 Sheet MPT
Drawer Paper Size:	8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, A3, B5
MPT Paper Size:	5.5" x 8.5", 8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, A3, B5, Custom (3.1" x 5.8" - 12.2" x 18.0")
Min / Max Paper Capacity:	FS-C8008N: 1,150 / 3,150 Sheets FS-C8008DN: 650 / 2,650 Sheets
Paper Weight:	16 - 24 lb Bond via Paper Drawers, 16 lb Bond - 121 lb Index via MPT
Input Materials:	Bond Paper, Transparencies, Labels, Cardstock, Postcards, Envelopes

## DUPLEX UNIT: FS-C8008DN

Paper Size:	8.5" x 11", 8.5" x 14", 11" x 17", A4, A3, A5, B4, B5
Paper Weight:	17 - 24 lb Bond

## HARD DISK DRIVE:

Enables Document Printing and e-MPS Functions: Private Print, Job Storage, Quick Copy, Proof and Hold, Virtual MailBoxes

## PAPER HANDLING OPTIONS:

### MULTI-POSITION STAPLE FINISHER: DF-31

Capacity:	Upper Tray: 600 Sheets, Middle Tray: 700 Sheets, Lower Tray: 700 Sheets
Paper Size:	8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, A3, B5, B4
Paper Weight:	17 - 34 lb Bond
Staple Capacity:	20 Sheets
Staple Position:	3 Positions: Upper Left, Bottom Left, Two Position Side
Dimensions / Weight:	25.6"W x 22.6"D x 45.6"H / 66.1 lbs

### STACKER: ST-30

Capacity:	3,000 Sheets
Paper Size:	8.5" x 11", 8.5" x 14", 11" x 17", A4, A3, B5, B4, Others (3.9" x 7.5" - 11.7" x 17.7")
Paper Weight:	17 lb Bond - 110 lb Index
Dimensions / Weight:	21.1"W x 17.6"D x 42.4"H / 63.9 lbs

### PAPER DRAWER: PF-30A

Paper Capacity:	Dual 500 sheets
Max. Drawers:	Max. Two PF-30A
Paper Weight:	16 - 24 lb Bond
Paper Size:	8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, A3, B5
Dimensions / Weight:	22"W x 22.3"D x 9.9"H / 42.1 lbs

### ADDITIONAL OPTIONS: Barcode Reader (BC-1)

## CONSUMABLES:

TK-800K:	Black Toner	25,000 Pages @ 5% Coverage*
TK-800Y:	Yellow Toner	10,000 Pages @ 5% Coverage*
TK-800M:	Magenta Toner	10,000 Pages @ 5% Coverage*
TK-800C:	Cyan Toner	10,000 Pages @ 5% Coverage*

\*Ships with 12,500 pages @5% Black Toner and 5,000 pages @5% Color Toner



Specifications and design are subject to change without notice. All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc.  
225 Sand Road, PO Box 40008,  
Fairfield, NJ 07004-0008, USA  
©2003 Kyocera Mita America, Inc.  
[www.kyoceramita.com](http://www.kyoceramita.com)

