

KM-4035 Specifications

BASIC SPECIFICATIONS:

| | |
|--------------------------|---|
| Configuration: | Desktop Digital Copier with Standard 500 x 2 Paper Drawers Plus 200 Sheet Multi-Purpose Tray, Standard Duplex, Optional Network Printing, Scanning and Network Fax. |
| Resolution: | 600 x 600 DPI Resolution / 256 Levels, Fast 1200 DPI Print Resolution |
| Copier Memory: | Standard 64MB RAM; Optional 20GB HDD |
| Magnification: | Full Size, 5 Reduction, 5 Enlargement Preset Ratios, Plus 25-400% Zoom |
| Electrical Requirements: | 120V, 60Hz, 12A |
| Dimensions: | 23"W x 25"D x 29"H |
| Weight: | 180 lbs |
| Max Monthly Volume: | 125,000 Pages Per Month |

OUTPUT SPEEDS:

| | |
|-------------------|--|
| Warm-Up Time: | Within 25 Seconds, Program During Warmup, Auto Start |
| First Copy Out: | 3.5 Seconds |
| Pages Per Minute: | 40 Letter, 23 Legal, 23 Ledger |

PAPER SUPPLY:

| | |
|---------------------------|--|
| Standard Paper Sources: | Dual 500 Sheet Drawers, 200 Sheet MPT, Auto Selection / Switching, Add Paper While Running |
| Drawer Paper Size: | 5.5" x 8.5" - 11" x 17" |
| MPT Paper Size: | 5.5" x 8.5" - 11" x 17" |
| Std / Max Paper Capacity: | 1,200 / 4,200 |
| Paper Weight: | 16-28 lb Bond via Paper Drawers, 16 lb Bond - 110 lb Index via MPT |
| Input Materials: | Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes |

DUPLEX UNIT:

| | |
|---------------|---------------------------------|
| Paper Size: | 5.5" x 8.5" - 11" x 17" |
| Paper Weight: | 17 - 21 lb Bond |
| Duplex Modes: | Standard 1:2, 2:2, Book: 2, 2:1 |

COPY FUNCTIONS:

| | |
|----------------------|---|
| Imaging Modes: | Text, Photo, Text / Photo, Auto, Manual, ECO |
| Continuous Copy: | Up to 999, Auto Reset to 1 |
| Additional Features: | Auto Magnification and Paper Select, Job Build, Job Queue, Batch Copy, Booklet Mode, Book Mode, Combine Image, Covers, Erase Mode, Image Overlay, Image Rotate, Image Reverse, Interrupt, 8 Job Programs, Margin Shift, Mirror Image, Page Numbering, Transparency Mode, Memo Mode, 100/1000 Management Codes, XY Zoom, Auto Centering OPTIONAL DOCUMENT MANAGEMENT: Store Documents, File Merge, Forms Composition, Repeat Copy |

PAPER HANDLING OPTIONS:

DOCUMENT PROCESSOR: SRDF-2

| | |
|-----------------------|--|
| Type: | Reversing Automatic Document Processor |
| Acceptable Originals: | 5.5" x 8.5" - 11" x 17", Mixed Size |
| Capacity: | 100 Sheet RADF / 50 Letter Size Originals Per Minute |
| Paper Weight: | 9 - 42 lb Bond |
| Dimensions / Weight: | 21.8"W x 18.8"D x 5.4"H / 23 lbs |

FINISHER: DF-71

| | |
|-----------------------|--|
| Stack Capacity: | Main Tray: 3,000 Sheets; Sub Tray: 250 Sheets |
| Paper Size: | Main: 8.5" x 11" - 11" x 17"; Sub: 5.5" x 8.5" - 11" x 17" |
| Paper Weight: | 12 lb Bond - 110 lb Index |
| Staple Capacity: | 50 Sheets: 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17" |
| Edge Staple Position: | 3 Positions: Top Left, Bottom Left, Left/Top Side |
| Punch: | Standard 2 and 3 Hole |
| Dimensions / Weight: | 27.1"W x 23.5"D x 41.5"H / 110 lbs |

SIMPLE FINISHER: DF-73

| | |
|-----------------------|---|
| Stack Capacity: | Main Tray: 1,000 Sheets |
| Paper Size: | Main: 8.5" x 11" - 11" x 17" |
| Paper Weight: | 17 - 34 lb Bond |
| Staple Capacity: | 30 Sheets: 8.5" x 11"; 20 Sheets: 8.5" x 14", 11" x 17" |
| Edge Staple Position: | 1 Position: Top Left |
| Dimensions / Weight: | 21.9"W x 20.7"D x 36.0"H / 55 lbs |

SADDLE STITCH FINISHER: DF-75

| | |
|-----------------------|---|
| Stack Capacity: | Main Tray: 1,000 Sheets |
| Paper Size: | Main: 8.5" x 11" - 11" x 17" |
| Paper Weight: | 16 lb Bond - 110 lb Index |
| Staple Capacity: | 50 Sheets: 8.5" x 11"; 25 Sheets: 8.5" x 14", 11" x 17" |
| Edge Staple Position: | 4 Positions: Top Left, Bottom Left, Left Side, Center |
| Saddle Stitch: | 8.5" x 11", 11" x 17"; Up to 10 Sheets |
| Punch: | Optional 2 and 3 Hole |
| Dimensions / Weight: | 28.3"W x 23.7"D x 39.4"H / 86 lbs |

INTERNAL FINISHER: DF-78

| | |
|-----------------------|---|
| Stack Capacity: | 500 Sheets |
| Paper Size: | 8.5" x 11" - 11" x 17" |
| Paper Weight: | 16 lb - 28 lb Bond |
| Staple Capacity: | 30 Sheets: 8.5" x 11"; 20 Sheets: 8.5" x 14", 11" x 17" |
| Edge Staple Position: | 1 Position |
| Dimensions / Weight: | 12.2"W x 16.0"D x 6.3"H / 19.8 lbs |

MULTI-BIN MAILBOX: M-2107

| | |
|----------------------|---|
| Number of Trays: | 7 |
| Tray Capacity: | 100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17" |
| Paper Weight: | 17 - 21 lb Bond |
| Dimensions / Weight: | 20.0"W x 15.7"D x 18.5"H / 22 lbs |

PUNCH UNIT: PH-2

| | |
|------------------|---------------------------|
| Paper Size: | 8.5" x 11" - 11" x 17" |
| Paper Weight: | 17 lb Bond - 110 lb Index |
| Number of Holes: | 2 and 3 |
| Weight: | 5.2 lbs |

LARGE CAPACITY TRAY: PF-75

| | |
|----------------------|---------------------------------|
| Paper Capacity: | 3,000 Sheets |
| Paper Weight: | 16 - 28 lb Bond |
| Paper Size: | 8.5" x 11" |
| Dimensions / Weight: | 23.2"W x 25"D x 12.3"H / 48 lbs |

DUAL PAPER DRAWERS: PF-70

| | |
|----------------------|-----------------------------------|
| Paper Capacity: | 2 x 500 Sheets |
| Paper Weight: | 16 - 28 lb Bond |
| Paper Size: | 5.5" x 8.5" - 11" x 17" |
| Dimensions / Weight: | 23.2"W x 25"D x 12.3"H / 57.4 lbs |

CONNECTIVITY OPTIONS:

PRINT/SCAN: PRINT/SCAN SYSTEM (U)

PRINT:

| | |
|------------------------------|---|
| Controller: | Embedded PowerPC750 / 500 MHz Controller |
| Printer Memory: | Standard 64MB, Upgradeable to 576MB via 100 Pin DIMMS, Optional Printer HDD, Standard CF Card Slot (Type 1) |
| Supported PDL/Emulations: | PRESCRIBE, PCL6 (PCL XL, PCL 5e), KPDL3 (PS3), KCGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer |
| Fonts: | 80 Outline Fonts for PCL XL/5e, 136 Outline Fonts for KPDL3, 1 Bitmap Font |
| Windows™ OS Compatibility: | Windows™ 95/98/Me/NT4.x/2000/XP/2003 |
| Novell™ OS Compatibility: | Novell NetWare™ 3.x/4.x/5.x/6.x |
| Mac OS Compatibility: | OS 8.x/9.x/10.x |
| UNIX OS Compatibility: | Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR) |
| Connectivity / Interface: | Standard 10/100BaseTX, Parallel IEEE1284, High Speed USB 2.0 |
| KUIO LV Expansion Slots (2): | Optional Printer Hard Disk Drive Optional IB-22 Enhanced Wireless NIC; IB-20 10/100BaseTX, 10Base2; IB-11 Serial Interface |

Supported Protocols:

| | |
|------------|---|
| Driver: | TCP/IP, IPX/SPX, AppleTalk, NetBEUI KX Driver for Windows™, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver |
| Utilities: | KM-NET Viewer, KM-NET for Clients, PDF Direct Print, KM-NET Printer Disk Manager, Network Advanced Setup Utilities, PRESCRIBE Utilities |

SCAN:

| | |
|----------------------|---|
| Resolution: | 200, 300, 400, 600 DPI |
| Scan Speed: | Up to 50 Sheets Per Minute |
| File Formats: | PDF, TIFF |
| Connectivity: | Standard NS-30 10/100BaseTX |
| Supported Protocols: | TCP/IP |
| Scanning Features: | KM Document Flow System - Document Management System, Scan to PC/File, Scan to Mac, Scan to E-Mail, TWAIN |
| Driver: | TWAIN Driver |
| Utilities: | KM DB-Assistant, KM Scanner File Utility, Scan to Mac Utility, KM Scanner Address Book, Address Book Editor, LDAP Converter Utility, Network Advanced Setup Utilities |

PRINTER HARD DISK DRIVE

Enables Document Printing and e-MPS Functions; Private Print, Job Storage, Quick Copy, Proof & Hold, Virtual MailBoxes

FAX/NETWORK FAX: FAX SYSTEM (J)

| | |
|----------------------|--|
| Compatibility: | Super G3 |
| Transmission Speed: | Approximately 3 Seconds per page |
| Modem Speed: | 33.6 Kbps with Auto Fallback |
| Data Compression: | JBIG, MMR, MR, MH |
| Fax Memory: | Std 8MB / Max 16MB |
| Driver: | KM Network Fax Driver |
| Utilities: | Address Book for NW Fax, Address Editor for Fax |
| Additional Features: | Duplex TX/RX, Confidential RX/TX, Polling, Broadcasting, 2 in 1 RX |

COPIER HARD DISK DRIVE: HD-70

Enables Advanced Copier Document Management; Synergy Box, Shared Data, Forms Gallery; Store up to 70,000 Pages, Repeat Copy, 1000 Management Codes

ADDITIONAL OPTIONS:

Data Security Kit (A), Job Separator (J-1402), 8MB Fax Memory Board (FM1-8MB), Stand



Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com/us.
All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
©2004 Kyocera Mita America, Inc.



www.kyoceramita.com/us